

**MARINE GENERATOR SPECIFICATIONS**



**KOHLER**<sup>®</sup>  
IN POWER. SINCE 1920.



Generator Model	kW*	Hz	Cylinder	RPM	Phase	Voltage	Amps	Length x Width x Height mm (in)		Weight (Wet) kg (lb)
								H – Housed / U – Unhoused		
21EKOZD	21	60	4	1800	3	120 / 208	73	H – 1197 (47.1) x 652.5 (25.7) x 711 (27.9) U – 1121 (44.1) x 577.5 (22.7) x 694 (27.3)	H – 480 (1059) U – 440 (970)	
						120 / 240	64			
					1	120 / 240	80			
						127 / 220	69			
					3	139 / 240	64			
						277 / 480	32			
17EFKOZD	17	50	4	1500	3	110 / 190	65			
						115 / 230	54			
					1	115 / 230	70			
						120 / 208	58			
					3	230 / 400	31			
						240 / 416	29			
24EKOZD	24	60	4	1800	1	120	200	H – 1197 (47.1) x 652.5 (25.7) x 711 (27.9) U – 1138 (44.8) x 577.5 (22.7) x 694 (27.3)	H – 489 (1078) U – 449 (990)	
						120 / 240	100			
20.5EFKOZD	21	50	4	1500	1	230	90			
						240	78			
24EKOZD	24	60	4	1800	3	120 / 208	84	H – 1197 (47.1) x 652.5 (25.7) x 711 (27.9) U – 1138 (44.8) x 577.5 (22.7) x 694 (27.3)	H – 489 (1078) U – 449 (990)	
						120 / 240	73			
					1	120 / 240	92			
						127 / 220	79			
					3	139 / 240	73			
						277 / 480	37			
20.5EFKOZD	20.5	50	4	1500	3	110 / 190	78			
						115 / 230	65			
					1	115 / 230	85			
						120 / 208	72			
					3	230 / 400	37			
						240 / 416	36			
24EKOZD	24	60	4	1800	1	120 / 240	133	H – 1303 (51.30) x 661 (26.04) x 778 (30.64) U – 1222 (48.13) x 643 (25.33) x 733 (28.86)	H – 607 (1339) U – 531 (1170)	
						120 / 208	111			
3	120 / 240	96								
	120 / 240	142								
1	127 / 220	105								
	3	139 / 240	96							
3	277 / 480	48								
	28EFKOZD	28	50	4	1500	1	230			122
240							96			
3						110 / 190	106			
						110 / 220	92			
1						115 / 230	117			
						120 / 208	97			
3	230 / 400	51								
	240 / 416	49								
24EKOZD	24	60	4	1800	1	120 / 240	152	H – 1354 (53.31) x 661 (26.04) x 778 (30.64) U – 1274 (50.17) x 643 (25.33) x 733 (28.86)	H – 637 (1404) U – 567 (1250)	
						120 / 208	139			
3	120 / 240	120								
	120 / 240	142								
1	127 / 220	131								
	3	139 / 240	120							
3	277 / 480	60								
	35EFKOZD	35	50	4	1500	1	230			152
240							133			
3						110 / 190	129			
						110 / 220	112			
1						115 / 230	130			
						120 / 208	121			
3	230 / 400	63								
	240 / 416	61								
24EKOZD	24	60	4	1800	1	220 / 380	65			
						220 / 380	65			

\*kW rating varies by voltage. Consult the generator spec sheet for more detail.

Generator Model	kW*	Hz	Cylinder	RPM	Phase	Voltage	Amps	Length x Width x Height mm (in)			Weight (Wet) kg (lb)
								H – Housed / U – Unhoused / R – Radiator			
33EFOZDJ	33	50	4	1500	3	110 / 190	125	H – 1633 (64.3) x 767 (30.2) x 1015 (39.9) U – 1524 (60) x 722 (28.4) x 960 (37.8) R – 1858 (73.2) x 827 (32.6) x 1265 (49.8)	H – 1025 (2260) U – 935 (2060) R – 957 (2110)*		
					1	115 / 230	143				
					3	220 / 380	63				
40EFOZDJ	40	50	4	1500	3	110 / 190	152	H – 1633 (64.3) x 767 (30.2) x 1015 (39.9) U – 1549 (60.9) x 738 (29) x 961 (37.8) R – 1884 (74.2) x 827 (32.5) x 1265 (49.8)	H – 1080 (2380) U – 971 (2140) R – 993 (2190)*		
					1	115 / 230	174				
					3	220 / 380	76				
50EFOZDJ	50	50	4	1500	3	110 / 190	190	H – 1690 (66.5) x 767 (30.2) x 1015 (39.9) U – 1606 (63.2) x 738 (29) x 961 (37.8) R – 1941 (76.4) x 827 (32.5) x 1265 (49.8)	H – 1114 (2456) U – 1005 (2216) R – 1028 (2266)*		
					1	115 / 230	196				
					3	220 / 380	95				
55EOZDJ	55	60	4	1800	3	120 / 208	191	H – 1633 (64.3) x 767 (30.2) x 1015 (39.9) U – 1549 (60.9) x 738 (29) x 961 (37.8) R – 1884 (74.2) x 827 (32.5) x 1265 (49.8)	H – 1090 (2404) U – 982 (2164) R – 1004 (2214)*		
					1	120 / 240	221				
					3	120 / 240	180				
45EFOZDJ	45	50	4	1500	3	110 / 190	171	H – 1633 (64.3) x 767 (30.2) x 1015 (39.9) U – 1549 (60.9) x 738 (29) x 961 (37.8) R – 1884 (74.2) x 827 (32.5) x 1265 (49.8)	H – 1090 (2404) U – 982 (2164) R – 1004 (2214)*		
					1	110 / 220	148				
					3	220 / 380	86				
65EOZDJ	65	60	4	1800	3	120 / 208	226	H – 1690 (66.5) x 767 (30.2) x 1015 (39.9) U – 1606 (63.2) x 738 (29) x 961 (37.8) R – 1941 (76.4) x 827 (32.5) x 1265 (49.8)	H – 1125 (2480) U – 1016 (2240) R – 1039 (2290)*		
					1	120 / 240	221				
					3	120 / 240	213				
55EFOZDJ	55	50	4	1500	3	110 / 190	209	H – 1690 (66.5) x 767 (30.2) x 1015 (39.9) U – 1606 (63.2) x 738 (29) x 961 (37.8) R – 1941 (76.4) x 827 (32.5) x 1265 (49.8)	H – 1125 (2480) U – 1016 (2240) R – 1039 (2290)*		
					1	110 / 220	181				
					3	220 / 380	105				
80EOZDJ	80	60	4	1800	3	120 / 208	278	H – 1754 (69) x 831 (32.7) x 1032 (40.6) U – 1657 (65.2) x 753 (29.6) x 999 (39.3) R – 1992 (78.4) x 890 (35) x 1277 (50.2)	H – 1270 (2800) U – 1148 (2530) R – 1179 (2600)*		
					1	120 / 240	241				
					3	120 / 240	262				
70EFOZDJ	70	50	4	1500	3	110 / 190	266	H – 1754 (69) x 831 (32.7) x 1032 (40.6) U – 1657 (65.2) x 753 (29.6) x 999 (39.3) R – 1992 (78.4) x 890 (35) x 1277 (50.2)	H – 1270 (2800) U – 1148 (2530) R – 1179 (2600)*		
					1	110 / 220	230				
					3	220 / 380	133				
99EOZDJ	99	60	4	1800	3	120 / 208	343	H – 1829 (72) x 831 (32.7) x 1032 (40.6) U – 1732 (68.2) x 753 (29.6) x 999 (39.3) R – 2067 (81.3) x 890 (35) x 1277 (50.2)	H – 1356 (2990) U – 1243 (2740) R – 1275 (2810)*		
					1	120 / 240	298				
					3	120 / 240	325				
80EFOZDJ	80	50	4	1500	3	110 / 190	304	H – 1829 (72) x 831 (32.7) x 1032 (40.6) U – 1732 (68.2) x 753 (29.6) x 999 (39.3) R – 2067 (81.3) x 890 (35) x 1277 (50.2)	H – 1356 (2990) U – 1243 (2740) R – 1275 (2810)*		
					1	110 / 220	262				
					3	220 / 380	152				
125EOZDJ	125	60	6	1800	3	120 / 208	434	H – 2205 (86.8) x 971 (38.2) x 1065 (41.9) U – 2068 (81.4) x 893 (35.2) x 1003 (39.5) R – 2466 (97.1) x 1129 (44.5) x 1275 (50.2)	H – 1683 (3710) U – 1515 (3340) R – 1578 (3478)		
					1	120 / 240	376				
					3	120 / 240	410				
100EFOZDJ	100	50	6	1500	3	110 / 190	380	H – 2205 (86.8) x 971 (38.2) x 1065 (41.9) U – 2068 (81.4) x 893 (35.2) x 1003 (39.5) R – 2466 (97.1) x 1129 (44.5) x 1275 (50.2)	H – 1683 (3710) U – 1515 (3340) R – 1578 (3478)		
					1	110 / 220	328				
					3	220 / 380	190				
150EOZDJ	150	60	6	1800	3	120 / 208	520	H – 2205 (86.8) x 971 (38.2) x 1065 (41.9) U – 2091 (82.3) x 893 (35.2) x 1003 (39.5) R – 2498 (98) x 1129 (44.5) x 1275 (50.2)	H – 1719 (3789) U – 1551 (3419) R – 1613 (3557)		
					1	120 / 240	451				
					3	120 / 240	492				
125EFOZDJ	125	50	6	1500	3	110 / 190	474	H – 2205 (86.8) x 971 (38.2) x 1065 (41.9) U – 2091 (82.3) x 893 (35.2) x 1003 (39.5) R – 2498 (98) x 1129 (44.5) x 1275 (50.2)	H – 1719 (3789) U – 1551 (3419) R – 1613 (3557)		
					1	120 / 208	433				
					3	110 / 220	409				
200EOZDJ	200	60	6	1800	3	120 / 208	694	H – 2661 (104.8) x 1048 (41.3) x 1174 (46.2) U – 2490 (98) x 970 (38.2) x 1086 (42.8)	H – 2147 (4733) U – 2067 (4558)		
					1	120 / 240	601				
					3	120 / 240	656				
175EFOZDJ	175	50	6	1500	3	110 / 190	665	H – 2661 (104.8) x 1048 (41.3) x 1174 (46.2) U – 2490 (98) x 970 (38.2) x 1086 (42.8)	H – 2147 (4733) U – 2067 (4558)		
					1	110 / 220	574				
					3	120 / 208	607				

\*kW rating varies by voltage. Consult the generator spec sheet for more detail.

**AMERICAS/CARIBBEAN**  
+1 920-565-3381  
+1 800-544-2444  
Fax 920-459-1646

**CHINA**  
+86 21 26062169  
+86 400 1808 900

**EUROPE  
MIDDLE EAST  
AFRICA**  
+31 168 331630

**ASIA PACIFIC**  
+65 6264 6422  
Fax +65 6264 6455

**INDIA**  
+91 80 42867000  
Fax +91 80 23615972

**New Zealand  
Australia**  
+61 88 29 02100

**KOHLERPOWER.COM**

Printed in U.S.A. G12-479 7/18 © 2018 by Kohler Co.